






Stil-Kamin 62/76 lifting doors

State: 30.08.2012






BRUNNER
made in germany

Dimension sheet | Stil-Kamin 62/76 lifting doors





... with mounting frame 50 mm





... with mounting frame 70 mm

Dimension sheet | **Stil-Kamin 62/76** lifting doors




... with door frame






...with mounting frame 50 mm and convection cladding

Dimension sheet | **Stil-Kamin 62/76 lifting doors**



...with mounting frame 70 mm and convection cladding



...with frame and convection cladding

Planning and installation

Stil-Kamin 62/76

Tested according to	EN 13229 W		EN 13229 W
Values measured at	nominal load		open door
Suitable for all construction types according to rules	OK		OK
Data for functional demonstration			
Rated heat power	kW	9	-
Firewood consumption	kg/h	3,0	3,0
Combustion performance	kW	11	13
Flue gas mass flow	g/s	12	70
Outlet temperature (before heating surface)	°C	325	-
Flue gas temperature after			
attached steel smoke hood	°C	190	120
1 x adjoining cast iron radiator (GNF10)	°C	135	-
6 x accumulation rings (MAS) ¹⁾	°C	205	-
adjoining ceramic accumulator ²⁾	°C	-	-
ceramic modular accumulator (KMS system)	°C	-	-
water boiler	°C	-	-
Necessary supply pressure	Pa	13	6
Combustion air consumption	m³/h	35	180
Combustion air connection Ø	mm	125	-
Heat distribution			
Insert / heating surface	%	60 / -	- / -
Glass (single / double)	%	40 / -	- / -
Boiler	%	-	-
Cross-section of gratings for max. warm air power			
Supply air	cm²	1500	0
Warm air	cm²	1500	0
Minimal oven surface for closed construction type			
Surface giving off heat	m²	4,5	-
Space inside oven chamber without / with convection cladding			
Distance to oven chamber wall	cm	8 / 0	8 / 0
Distance to floor	cm	-	-
Heat insulation without / with ³⁾ air gratings / with convection cladding			
Wall	cm	18 / 14 / 3	18 / 14 / 3
Floor	cm	4 / 2 / 2	4 / 2 / 2
Ceiling	cm	22 / 16 / 16	22 / 16 / 16
Insulation of additional fire door DHT	cm	-	-
Brick lining of protected walls	cm	10	10
Weight			
Fireplace + burning chamber	kg	202 + 104	
meets requirement limit values for			
Germany / Austria / Switzerland / Norway		1.BImSchV (Stufe 2) / 15a BVG / LRV / -	

1) Throttle flap recommended

2) Approximate value, must be calculated eventually

3) Values with air gratings, stove casing is heat conducting

Ulrich Brunner GmbH
 Zellhuber Ring 17 -18
 D-84307 Eggenfelden
 Phone: +49 / (0)87 21 / 7 71-0
 Fax: +49 / (0)87 21 / 7 71-100
 info@brunner.de | www.brunner.de

BRUNNER®

BRUNNER products are offered and sold only by qualified dealers and service centres.
 Subject to technical and assortment changes. Errors excepted. (08/12)