BRUNNER TILE STOVES



HKD 2.6

State: 30.08.2012

























Dimension sheet | HKD 2.6





Planning and installation

HKD 2.6

Tested according to		EN 13229 W	EN 13229 WA
Values measured at		nominal load	accumulation
Suitable for all construction types according to rules		OK	OK
Data for functional demonstration			
Rated heat power	kW	9	-
Firewood consumption	kg/h	2,5	4
Combustion performance	kW	11	17
Flue gas mass flow	g/s	10	17
Outlet temperature (before heating surface)	°C	495	520
Flue gas temperature after			
attached steel smoke hood	°C	-	-
1 x adjoining cast iron radiator (GNF10)	°C	122	165
6 x accumulation rings (MAS) 1)	°C	220	-
4,5 m adjoining ceramic accumulator ²⁾	°C	-	180
3,5 m ceramic modular accumulator (KMS system)	°C	-	180
water boiler	°C	210	-
Necessary supply pressure	Pa	12	15
Combustion air consumption	m³/h	25	45
Combustion air connection Ø	mm	125	125
Heat distribution			
Insert / heating surface	%	45 / 35 - 45	45 / 35 - 45
Glass (single / double)	%	20 / 10	20 / 10
Boiler	%	-	-
Cross-section of gratings for max. warm air power			
Supply air	cm ²	1300	1300
Warm air	cm ²	1300	1300
Space inside oven chamber			
Distance to oven chamber wall	cm	6	6
Distance to floor	cm	15	15
Heat insulation without / with ³⁾ air gratings	OIII	10	
Wall	cm	12 / 8	12/8
Floor	cm	0	0
Ceiling	cm	22 / 16	22 / 16
Insulation of additional fire door DHT	cm	6	6
Brick lining of protected walls	cm	10	10
	V1		
Weight Fireplace + burning chamber	kg 224 + 63		
<u> </u>	kg	224	T 00
meets requirement limit values for	1 PlmSoh\/ (Stufo 2) / 15a P\/C / L D\/ /		
Germany / Austria / Switzerland / Norway	1.BImSchV (Stufe 2) / 15a BVG / LRV / -		

- 1) Throttle flap recommended
- 2) Approximate value, must be calculated eventually
- 3) Values with air gratings, stove casing is heat conducting

Ulrich Brunner GmbH Zellhuber Ring 17 -18 D-84307 Eggenfelden Phone: +49 / (0)87 21 / 7 71-0 Fax: +49 / (0)87 21 / 7 71-100 info@brunner.de | www.brunner.de

